

JSR Ordering Code

1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20
J	S	R	1	0	3	F	3	4	4	F	B	2	8	0	5	0	D	B	A
↓	↓			↓		↓		↓		↓	↓	↓			↓		↓	↓	↓
①				②		③		④		⑤	⑥	⑦			⑧				⑨

1	Product series	JSR	5	Tolerance of B Value	F=±1% G=±2% H=±3%	9	Wire Type	C=UL4413 TC D=UL4413 TS P=Other
2	R25°C Resistance	502=5KΩ 103=10KΩ 474=470KΩ	6	Definition of B Value	A=25/50 B=25/85	10	TC & Connected	B = 並線 + 沾錫 C = 並線 + 端子 F = 分線 + 沾錫 G = 並線 + 沾錫 H = 並線 + 連接器
3	R25°C Resistance Tolerance	F=±1% G=±2% H=±3% J=±5%	7	Wire Gauge	22=22AWG 28=28AWG			
4	B Value	344 = 3435 405 = 4050	8	Total Length	025=25mm 145=145mm	A	剝線/分切長度	A:剝線長度=3.5±0.5mm , 分切長度≥10.0mm C:剝線 長度=3.0±0.5mm , 分切 長度≥20.0mm

Example

JSR103F344FB28105SB

JSR104J410HA26120PB

ATBEL TECHNOLOGY CORP. TEL:886-2-87518083 FAX:886-2-87512032