

Standard Series 10mm

Model Number	Max. continuous voltage		Reference current (mA)	Voltage at reference current		Voltage at class current (8/20 μ s)		Max peak current (8/20 μ s 1 time) (A)	Energy		Max. capacitance (pF)
	r.m.s. (v)	d.c. (v)		Min. (v)	Max. (v)	Class Current (A)	Max. Clamping Voltage (V)		10/1000 μ s (J)	8/20 μ s (J)	
10D 180K	11	14	1.0	16	20	5	36	500	2.1	2.1	5600
10D 220K	14	18	1.0	20	24	5	43	500	2.5	2.5	4250
10D 270K	17	22	1.0	24	30	5	53	500	3.0	3.0	3700
10D 330K	20	26	1.0	30	36	5	65	500	4.0	4.0	2000
10D 390K	25	31	1.0	35	43	5	77	500	4.6	4.6	2400
10D 470K	30	38	1.0	42	52	5	93	500	5.5	5.5	2100
10D 560K	35	45	1.0	50	62	5	110	500	7.0	7.0	1400
10D 680K	40	56	1.0	61	75	5	135	500	8.2	8.2	1250
10D 820K	50	65	1.0	74	90	25	135	2500	12.0	12.0	1200
10D 101K	60	85	1.0	90	110	25	165	2500	15.0	15.0	500
10D 121K	75	100	1.0	108	132	25	200	2500	18.0	18.0	830
10D 151K	95	125	1.0	135	165	25	250	2500	22.0	22.0	670
10D 181K	115	150	1.0	162	198	25	300	2500	27.0	27.0	560
10D 201K	130	170	1.0	185	225	25	340	2500	30.0	30.0	250
10D 221K	140	180	1.0	198	242	25	360	2500	32.0	32.0	450
10D 241K	150	200	1.0	216	264	25	395	2500	35.0	35.0	420
10D 271K	175	225	1.0	243	297	25	455	2500	40.0	40.0	370
10D 301K	190	250	1.0	270	330	25	500	2500	40.0	40.0	330
10D 331K	210	275	1.0	297	363	25	550	2500	43.0	43.0	300
10D 361K	230	300	1.0	324	396	25	595	2500	47.0	47.0	280
10D 391K	250	320	1.0	351	429	25	650	2500	60.0	60.0	260
10D 431K	275	350	1.0	387	473	25	710	2500	65.0	65.0	230
10D 471K	300	385	1.0	423	517	25	775	2500	70.0	70.0	210
10D 511K	320	415	1.0	459	561	25	845	2500	70.0	70.0	200
10D 561K	350	460	1.0	504	616	25	925	2500	70.0	70.0	180
10D 621K	385	505	1.0	558	682	25	1025	2500	70.0	70.0	160
10D 681K	420	560	1.0	612	748	25	1120	2500	70.0	70.0	150
10D 751K	460	615	1.0	675	825	25	1240	2500	75.0	75.0	130
10D 781K	485	640	1.0	702	858	25	1290	2500	80.0	80.0	130
10D 821K	510	670	1.0	738	902	25	1355	2500	85.0	85.0	110
10D 911K	550	745	1.0	819	1001	25	1250	2500	93.0	93.0	130
10D 102K	625	825	1.0	900	1100	25	1650	2500	102.0	102.0	140
10D 112K	680	895	1.0	990	1210	25	1815	2500	115.0	115.0	155