

Standard Series 14mm

Model Number	Max. continuous voltage		Reference current (mA)	Voltage at reference current		Voltage at class current (8/20 μ s)		Max peak current (8/20 μ s 1 time) (A)	Energy		Max. capacitance (pF)
	r.m.s. (v)	d.c. (v)		Min. (v)	Max. (v)	Class Current (A)	Max. Clamping Voltage (V)		10/1000 μ s (J)	8/20 μ s (J)	
14D 180K	11	14	1.0	16	20	10	36	1000	4.0	4.0	11100
14D 220K	14	18	1.0	20	24	10	43	1000	5.0	5.0	9100
14D 270K	17	22	1.0	24	30	10	53	1000	6.0	6.0	7400
14D 330K	20	26	1.0	30	36	10	65	1000	7.5	7.5	6100
14D 390K	25	31	1.0	35	43	10	77	1000	8.6	8.6	5100
14D 470K	30	38	1.0	42	52	10	93	1000	10.0	10.0	4300
14D 560K	35	45	1.0	50	62	10	110	1000	11.0	11.0	3600
14D 680K	40	56	1.0	61	75	10	135	1000	14.0	14.0	2900
14D 820K	50	65	1.0	74	90	50	135	4500	22.0	22.0	2400
14D 101K	60	85	1.0	90	110	50	165	4500	28.0	28.0	1000
14D 121K	75	100	1.0	108	132	50	200	4500	32.0	32.0	1700
14D 151K	95	125	1.0	135	165	50	250	4500	40.0	40.0	1300
14D 181K	115	150	1.0	162	198	50	300	4500	50.0	50.0	1100
14D 201K	130	170	1.0	185	225	50	340	4500	57.0	57.0	500
14D 221K	140	180	1.0	198	242	50	360	4500	60.0	60.0	900
14D 241K	150	200	1.0	216	264	50	395	4500	63.0	63.0	830
14D 271K	175	225	1.0	243	297	50	455	4500	70.0	70.0	740
14D 301K	190	250	1.0	270	330	50	500	4500	77.0	77.0	670
14D 331K	210	275	1.0	297	363	50	550	4500	85.0	85.0	610
14D 361K	230	300	1.0	324	396	50	595	4500	93.0	93.0	560
14D 391K	250	320	1.0	351	429	50	650	4500	100.0	100.0	510
14D 431K	275	350	1.0	387	473	50	710	4500	115.0	115.0	460
14D 471K	300	385	1.0	423	517	50	775	4500	125.0	125.0	430
14D 511K	320	415	1.0	459	561	50	845	4500	125.0	125.0	390
14D 561K	350	460	1.0	504	616	50	925	4500	125.0	125.0	360
14D 621K	385	505	1.0	558	682	50	1025	4500	125.0	125.0	320
14D 681K	420	560	1.0	612	748	50	1120	4500	130.0	130.0	290
14D 751K	460	615	1.0	675	825	50	1240	4500	143.0	143.0	270
14D 781K	485	640	1.0	702	858	50	1290	4500	148.0	148.0	260
14D 821K	510	670	1.0	738	902	50	1355	4500	157.0	157.0	240
14D 911K	550	745	1.0	819	1001	50	1250	4500	175.0	175.0	220
14D 102K	625	825	1.0	900	1100	50	1650	4500	190.0	190.0	200
14D 112K	680	895	1.0	990	1210	50	1815	4500	213.0	213.0	180
14D 122K	750	990	1.0	1080	1320	50	1980	4500	337.0	337.0	150
14D 182K	1100	1465	1.0	1620	1980	50	2970	4500	337.0	337.0	100