

Standard Series 18mm

	Max. continuous voltage		Reference current	Voltage at reference current		Voltage at class current (8/20 μ s)		Max peak current (8/20 μ s 1 time)	Energy		Max. capacitance
Model Number	r.m.s. (v)	d.c. (v)	(mA)	Min. (v)	Max. (v)	Class Current (A)	Max. Clamping Voltage (V)	(A)	10/1000 μ s (J)	8/20 μ s (J)	(pF)
18D 180K	11	14	1.0	16	20	15	36	1500	9.0	9.0	22000
18D 220K	14	18	1.0	20	24	15	43	1500	12.0	12.0	12500
18D 270K	17	22	1.0	24	30	15	53	1500	16.0	16.0	10250
18D 330K	20	26	1.0	30	36	15	65	1500	21.0	21.0	9300
18D 390K	25	31	1.0	35	43	15	77	1500	24.0	24.0	7000
18D 470K	30	38	1.0	42	52	15	93	1500	31.0	31.0	4500
18D 560K	35	45	1.0	50	62	15	110	1500	39.0	39.0	5300
18D 680K	40	56	1.0	61	75	15	135	1500	44.0	44.0	4700
18D 820K	50	65	1.0	74	90	75	135	5500	36.0	36.0	5500
18D 101K	60	85	1.0	90	110	75	165	5500	43.0	43.0	3200
18D 121K	75	100	1.0	108	132	75	200	5500	53.0	53.0	2700
18D 151K	95	125	1.0	135	165	75	250	5500	68.0	68.0	2200
18D 181K	115	150	1.0	162	198	75	300	5500	83.0	83.0	1400
18D 201K	130	170	1.0	185	225	75	340	5500	93.0	93.0	1600
18D 221K	140	180	1.0	198	242	75	360	5500	98.0	98.0	1450
18D 241K	150	200	1.0	216	264	75	395	5500	106.0	106.0	1350
18D 271K	175	225	1.0	243	297	75	455	5500	125.0	125.0	1200
18D 301K	190	250	1.0	270	330	75	500	5500	134.0	134.0	1050
18D 331K	210	275	1.0	297	363	75	550	5500	148.0	148.0	500
18D 361K	230	300	1.0	324	396	75	595	5500	161.0	161.0	900
18D 391K	250	320	1.0	351	429	75	650	5500	178.0	178.0	400
18D 431K	275	350	1.0	387	473	75	710	5500	188.0	188.0	750
18D 471K	300	385	1.0	423	517	75	775	5500	218.0	218.0	680
18D 511K	320	415	1.0	459	561	75	845	5500	218.0	218.0	630
18D 561K	350	460	1.0	504	616	75	925	5500	218.0	218.0	580
18D 621K	385	505	1.0	558	682	75	1025	5500	218.0	218.0	530
18D 681K	420	560	1.0	612	748	75	1120	5500	218.0	218.0	250
18D 751K	460	615	1.0	675	825	75	1240	5500	228.0	228.0	430
18D 781K	485	640	1.0	702	858	75	1290	5500	253.0	253.0	410
18D 821K	510	670	1.0	738	902	75	1355	5500	263.0	263.0	400
18D 911K	550	745	1.0	819	1001	75	1250	5500	280.0	280.0	360
18D 102K	625	825	1.0	900	1100	75	1650	5500	308.0	308.0	330
18D 112K	680	895	1.0	990	1210	75	1815	5500	340.0	340.0	290