

Standard Series 20mm

Model Number	Max. continuous voltage		Reference current (mA)	Voltage at reference current		Voltage at class current (8/20 μ s)		Max peak current (8/20 μ s 1 time) (A)	Energy		Max. capacitance (pF)
	r.m.s. (v)	d.c. (v)		Min. (v)	Max. (v)	Class Current (A)	Max. Clamping Voltage (V)		10/1000 μ s (J)	8/20 μ s (J)	
20D 180K	11	14	1.0	16	20	20	36	2000	11.0	11.0	28250
20D 220K	14	18	1.0	20	24	20	43	2000	14.0	14.0	18250
20D 270K	17	22	1.0	24	30	20	53	2000	18.0	18.0	12000
20D 330K	20	26	1.0	30	36	20	65	2000	23.0	23.0	11250
20D 390K	25	31	1.0	35	43	20	77	2000	26.0	26.0	8250
20D 470K	30	38	1.0	42	52	20	93	2000	33.0	33.0	7400
20D 560K	35	45	1.0	50	62	20	110	2000	41.0	41.0	6250
20D 680K	40	56	1.0	61	75	20	135	2000	46.0	46.0	5400
20D 820K	50	65	1.0	74	90	100	135	6500	38.0	38.0	4900
20D 101K	60	85	1.0	90	110	100	165	6500	45.0	45.0	5500
20D 121K	75	100	1.0	108	132	100	200	6500	55.0	55.0	3300
20D 151K	95	125	1.0	135	165	100	250	6500	70.0	70.0	2700
20D 181K	115	150	1.0	162	198	100	300	6500	85.0	85.0	2200
20D 201K	130	170	1.0	185	225	100	340	6500	95.0	95.0	1000
20D 221K	140	180	1.0	198	242	100	360	6500	100.0	100.0	1400
20D 241K	150	200	1.0	216	264	100	395	6500	108.0	108.0	1650
20D 271K	175	225	1.0	243	297	100	455	6500	127.0	127.0	1250
20D 301K	190	250	1.0	270	330	100	500	6500	136.0	136.0	1300
20D 331K	210	275	1.0	297	363	100	550	6500	150.0	150.0	1200
20D 361K	230	300	1.0	324	396	100	595	6500	163.0	163.0	1100
20D 391K	250	320	1.0	351	429	100	650	6500	180.0	180.0	500
20D 431K	275	350	1.0	387	473	100	710	6500	190.0	190.0	930
20D 471K	300	385	1.0	423	517	100	775	6500	220.0	220.0	850
20D 511K	320	415	1.0	459	561	100	845	6500	220.0	220.0	780
20D 561K	350	460	1.0	504	616	100	925	6500	220.0	220.0	710
20D 621K	385	505	1.0	558	682	100	1025	6500	220.0	220.0	650
20D 681K	420	560	1.0	612	748	100	1120	6500	220.0	220.0	600
20D 751K	460	615	1.0	675	825	100	1240	6500	230.0	230.0	530
20D 781K	485	640	1.0	702	858	100	1290	6500	255.0	255.0	510
20D 821K	510	670	1.0	738	902	100	1355	6500	265.0	265.0	250
20D 911K	550	745	1.0	819	1001	100	1250	6500	282.0	282.0	440
20D 102K	625	825	1.0	900	1100	100	1650	6500	310.0	310.0	400
20D 112K	680	895	1.0	990	1210	100	1815	6500	342.0	342.0	360
20D 122K	750	990	1.0	1080	1320	100	1980	6500	383.0	383.0	320
20D 182K	1100	1465	1.0	1620	1980	100	2970	6500	625.0	625.0	220