

L Type HS Series 25mm

SPECIFICATION

Model Number	Max. Continuous Voltage		Reference Current	Voltage At Reference Current		Voltage at Class Current (8/20 μ s)		Peak Current (8/20 μ s)		Energy		Max. Capacitance
	r.m.s. (V)	d.c. (V)		Min. (V)	Max. (V)	Class Current (A)	Max. Clamping Voltage (V)	I _n (A) 15time	I _{max} (A) 1time	10/1000 μ s (J)	8/20 μ s (J)	
25D 180K	11	14	1	16	20	30	36	2000	5000	20	20	45000
25D 220K	14	18	1	20	24	30	43	2000	5000	25	25	29000
25D 270K	17	22	1	24	30	30	53	2000	5000	30	30	26500
25D 330K	20	26	1	30	36	30	65	2000	5000	35	35	18000
25D 390K	25	31	1	35	43	30	77	2000	5000	40	40	13500
25D 470K	30	38	1	42	52	30	93	2000	5000	50	50	11500
25D 560K	35	45	1	50	62	30	110	2000	5000	60	60	10500
25D 680K	40	56	1	61	75	30	135	2000	5000	70	70	9050
25D 820K	50	65	1	74	90	150	135	10000	20000	80	80	7700
25D 101K	60	85	1	90	110	150	165	10000	20000	100	100	6300
25D 121K	75	100	1	108	132	150	200	10000	20000	120	120	5200
25D 151K	95	125	1	135	165	150	250	10000	20000	160	160	4300
25D 181K	115	150	1	162	198	150	300	10000	20000	175	175	3500
25D 201K	130	170	1	185	225	150	340	10000	20000	190	190	3200
25D 221K	140	180	1	198	242	150	360	10000	20000	200	200	2900
25D 241K	150	200	1	216	264	150	395	10000	20000	220	220	2650
25D 271K	175	225	1	243	297	150	455	10000	20000	255	255	2400
25D 301K	190	250	1	270	330	150	500	10000	20000	275	275	2100
25D 331K	210	275	1	297	363	150	550	10000	20000	300	300	1900
25D 361K	230	300	1	324	396	150	595	10000	20000	330	330	1750
25D 391K	250	320	1	351	429	150	650	10000	20000	360	360	1600
25D 431K	275	350	1	387	473	150	710	10000	20000	380	380	1500
25D 471K	300	385	1	423	517	150	775	10000	20000	400	400	1400
25D 511K	320	415	1	459	561	150	845	10000	20000	420	420	1250
25D 561K	350	460	1	504	616	150	925	10000	20000	440	440	1150
25D 621K	385	505	1	558	682	150	1025	10000	20000	450	450	1050
25D 681K	420	560	1	612	748	150	1120	10000	20000	460	460	950
25D 711K	440	585	1	639	781	150	1180	10000	20000	485	485	900
25D 751K	460	615	1	675	825	150	1240	10000	20000	510	510	850
25D 781K	485	640	1	702	858	150	1290	10000	20000	530	530	800
25D 821K	510	670	1	738	902	150	1355	10000	20000	570	570	750
25D 911K	550	745	1	819	1001	150	1500	10000	20000	620	620	700
25D 951K	575	760	1	855	1045	150	1570	10000	20000	620	620	700
25D 102K	625	825	1	900	1100	150	1650	10000	20000	685	685	650
25D 112K	680	895	1	990	1210	150	1815	10000	20000	770	770	600
25D 122K	750	990	1	1080	1320	150	1980	10000	20000	770	770	550